MECTEC TT150-RF ID

TT150 - RF ID

With TT150-RF ID you have the ideal solution for full A5 Print, Apply and RF ID-encoding – according to GS1 UHF Gen 2 standards and specifications!

The TT150 has the reliable, robust and easy to use design - as seen on all the Mectec family machines. It is proven to give you 24 hours reliable labelling for many years to come - even in the most harsh industrial environments!



Labelling pallets or large boxes with A5 / A6 portrait or landscape labels



Printer and applicator in right hand version

Handheld terminal TG300 (optional)

Printer Control Unit PCU III

TECHNICAL DATA

Type of applicator:	Tamp/Tamp-Blow. The blow can be switched off
Tamp size:	150 x 210 mm
Print speed:	Up to 275 mm/sec
Resolution:	8 or 12 dots/mm 200/300 DPI
Interface:	2 x RS232, 1 x RS485, 1 x USB 2.0 (Ethernet optional)
RF ID System:	868 and 915 MHz, dual frequency support. Full UHF Gen 2 Compliance Automatic or Custom Tag programming
Overall dimensions:	667 x 685 x 318 mm (l x h x w) - P & A 406 x 265 x 128 mm (l x h x w) - PCU III
Controller functions:	On-Line and Stand alone operation, 2 x 20 characters display, 9 keys, 11 status LEDs. 24 inputs, 26 outputs. Real timelock, counters, date offsets and much more...!

FAST FACTS

Printer:	6″ Thermal Transfer
Application:	Side, top or bottom labelling Stationary objects preferred
Label size:	110 x 110 - 150 x 210 mm
Distance:	0 - 360 mm

Available in both right- and left hand version!

ACCESSORIES

- TG300 - Handheld terminal
- Warning Low Level Media
- Cabinets
- Label Check in the Applicator Pad
- Flashlight/Beacon
- Check scanner
- Fixed or adjustable stands

CJSC "Intech Systems Group"
Moscow, 2 proezd Perova Polya, h.2, bld. 4.
Tel/fax: (495) 734-99-18, e-mail: sales@intechsystems.ru
www.intechsystems.ru

MECTEC